Ordering number:EN3331

NPN Triple Diffused Planar Silicon Transistor

2SC4460

500V/15A Switching Regulator Applications

Features

- High breakdown voltage, high reliability.
- Fast switching speed.
- Wide ASO.
- Adoption of MBIT process.
- Micaless package facilitating mounting.

Package Dimensions

unit:mm

2039D



Specifications

Absolute Maximum Ratings at Ta = 25˚C

Parameter	Symbol	Conditions	Ratings	Unit
Collector-to-Base Voltage	V_{CBO}		800	V
Collector-to-Emitter Voltage	V_{CEO}		500	V
Emitter-to-Base Voltage	V_{EBO}		7	V
Collector Current	I_C		15	A
Collector Current (Pulse)	I_{CP}	PW≤300μs, duty cycle≤10%	25	A
Base Current	I_B		4	A
Collector Dissipation	P_C		3	W
		Tc=25˚C	55	W
Junction Temperature	Tj		150	˚C
Storage Temperature	Tstg		–55 to +150	˚C

Electrical Characteristics at Ta = 25˚C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Collector Cutoff Current	I_{CBO}	V_{CB}=500V, I_E=0			10	μA
Emitter Cutoff Current	I_{EBO}	V_{EB}=5V, I_C=0			10	μA
DC Current Gain	$h_{FE}1$	V_{CE}=5V, I_C=1.2A	15*		50*	
	$h_{FE}2$	V_{CE}=5V, I_C=6A	8			

* : For the $h_{FE}1$ of the 2SC4460, specify two ranks or more in principle.

15 L 30	20 M 40	30 N 50

■ Any and all SANYO products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your SANYO representative nearest you before using any SANYO products described or contained herein in such applications.

■ SANYO assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges,or other parameters) listed in products specifications of any and all SANYO products described or contained herein.

SANYO Electric Co.,Ltd. Semiconductor Bussiness Headquaters

TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110-8534 JAPAN

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Gain-Bandwidth Product	f_T	V_{CE}=10V, I_C=1.2A		18		MHz
Output Capacitance	C_{ob}	V_{CB}=10V, f=1MHz		160		pF
Collector-to-Emitter Saturation Voltage	$V_{CE(sat)}$	I_C=6A, I_B=1.2A			1.0	V
Base-to-Emitter Saturation Voltage	$V_{BE(sat)}$	I_C=6A, I_B=1.2A			1.5	V
Collector-to-Base Breakdown Voltage	$V_{(BR)CBO}$	I_C=1mA, I_E=0	800			V
Collector-to-Emitter Breakdown Voltage	$V_{(BR)CEO}$	I_C=5mA, R_{BE}=∞	500			V
Emitter-to-Base Breakdown Voltage	$V_{(BR)EBO}$	I_E=1mA, I_C=0	7			V
Collector-to-Emitter Sustain Voltage	$V_{CEX(sus)}$	I_C=5A, I_{B1}=–I_{B2}=2A, L=500μH, Clamped	500			V
Turn-ON Time	t_{on}	V_{CC}=200V, 5I_{B1}=–2.5I_{B2}=I_C=7A, R_L=28.6Ω			0.5	μs
Storage Time	t_{stg}	V_{CC}=200V, 5I_{B1}=–2.5I_{B2}=I_C=7A, R_L=28.6Ω			3.0	μs
Fall Time	t_f	V_{CC}=200V, 5I_{B1}=–2.5I_{B2}=I_C=7A, R_L=28.6Ω			0.3	μs

Switching Time Test Circuit



Unit (resistance : Ω, capacitance : F)










VBE(sat) – IC
IC/IB=5
Ta=–40°C
25°C
–40°C
Base-to-Emitter Saturation Voltage,VBE(sat) – V
Collector Current,IC – A


SW. Time – IC
tstg
ton
tf
Switching Time,SW Time – μs
Collector Current,IC – A


Forward Bias A S O
ICP
IC
<50μs
100μs
1ms
10ms
PC=55W
DC operation
Tc=25°C
Single pulse
Collector Current,IC – A
Collector-to-Emitter Voltage,VCE – V


Reverse Bias A S O
Test Circuit
IC
IB1
IB2
VR
–5V
VCC=20V
L
IB2=–2A
L=100μH
Tc=25°C
Collector Current,IC – A
Collector-to-Emitter Voltage,VCE – V


Rth(t) – t
Tc=25°C
Transient Thermal Resistance,Rth(t) – °C/W
Time,t – ms


PC – Tc
Collector Dissipation,PC – W
Case Temperature,Tc – °C

- Specifications of any and all SANYO products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- SANYO Electric Co., Ltd. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all SANYO products(including technical data,services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of SANYO Electric Co., Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO product that you intend to use.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of December, 1998. Specifications and information herein are subject to change without notice.

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.